



Product Data Sheet

PM811-G2

Linear mode, boxed power supply, EN50131 grade 2 certified, 12VDC 1A

Certified Gr.2

Suitable for use in systems designed to comply with EN50131-6:2008 to Grade 2 and Environmental Class II requiring 7Ah standby battery capacity.

Protection

Comprehensive protection is built-in as standard including mains transient filtering, transformer thermal fuse, electronic output overload protection and fuses on the load and battery outputs.



Standard Features

- Fault signals for loss of mains, power supply fault and battery low voltage warning
- Battery deep discharge protection
- Tamper switch
- Protection against reverse battery connection
- Thermal protection of power circuitry
- Powder coated steel housing
- EN50131-6:2008 certified

PM811-G2

Linear mode, boxed power supply, EN50131 grade 2 certified, 12VDC 1A

Specifications

Input voltage	230 VAC
	+10% / -15%
Output voltage	13.8 VDC
Output current	
Total available	1A + 0.5A to charge standby battery (typically 7A)
Mains	1A
Battery for 12 hours	0.6 A with 7 A battery
Output Ripple	<220mV pk – pk max @ 230Vac
Max. battery size	7.2 A
Battery recharge time	< 72 hours to 80%
Deep discharge protection	Battery disconnect at 10.6 V battery terminal voltage
Protection	Reverse battery connection protection
Fuse	
Load	F1.6A
Battery	F1.6A
Operating temperature	-10 to +40°C
Storage temperature	-20 to +80°C
Relative humidity	75%
Housing (steel) powder coated	1.2 mm
Dimensions (W x H x D)	230 x 200 x 80 mm
Weight without battery	2.7 kg
Certifications	EN50131-6:2008 Environmental Class II

Ordering Information

Part No.	Description
PM811-G2	Linear mode, boxed power supply, EN50131 grade 2 certified, 12VDC 1A

