



## Product Data Sheet

# PM812-G3

Linear mode, boxed power supply, EN50131 grade 3 certified, 12VDC 1.5A

### EN certified

Suitable for use in systems designed to comply with EN50131-6:2008 to Grade 3 and Environmental Class II requiring 17Ah standby battery capacity.

### Protection

Comprehensive protection is built-in as standard including mains transient filtering, transformer thermal fuse, electronic output overload protection and fuses on the load and battery outputs.



### Standard Features

- Intelligent active battery monitoring
- Fault signals for loss of mains, battery fail and power supply fault
- Battery deep discharge protection
- Tamper switch
- Protection against reverse battery connection
- Electronic overload protection
- Transformer thermal fuse
- Powder coated steel housing
- EN50131-6:2008 grade 3 certified

# PM812-G3

Linear mode, boxed power supply, EN50131 grade 3 certified, 12VDC 1.5A

## Specifications

Input voltage	230 VAC
	+10% / -15%
Output voltage	13.8 VDC
Output current	
Total available	1.5A+0.5A to charge standby battery (typically 17A)
Mains	1.4 A
Battery for 12 hours	1.4 A with 17 A battery
Battery for 24 hours	0.7 A with 17 A battery
Output Ripple	<100 mV pk – pk max @ 230 VAC
Max. battery size	17 A
Battery recharge time	< 24 hours to 80%
Deep discharge protection	Battery disconnect at 10.5 V battery terminal voltage
Protection	Reverse battery connection protection
Fuse	
Load	F2.0A
Battery	F2.0A
Operating temperature	-10 to +40°C
Storage temperature	-20 to +80°C
Relative humidity	75%
Housing (steel) powder coated	1.2 mm
Dimensions (W x H x D)	330 x 275 x 80 mm
Weight without battery	4.7 kg
Certifications	EN50131-6:2008 Grade 3 Environmental Class II

## Ordering Information

Part No.	Description
PM812-G3	Linear mode, boxed power supply, EN50131 grade 3 certified, 12VDC 1.5A

