



Product Data Sheet

DM2010

2000 Series Addressable Manual Call Point (RED)

General

The DM2010 is a surface mount, RED addressable 2000 Series manual call point with a high strength plastic housing. The LED indicator provides visual confirmation of alarm initiation. The test key (included with each unit) facilitates functional testing of the call point. The manual call point is delivered complete with glass, but a resettable element can be installed as an option at any time.

Installation

The DM2010 may be used with the GE Security 2000/1200 series fire panels via a two-wire communication loop that provides power and control data. The call point's address is conveniently set with a dip switch. The address setting is non-volatile and will not be lost in the event of a power outage.

The manual call point utilizes the 2000 series advanced digital data communications protocol that ensures the integrity of the data communications with extensive error correction algorithms. Fast response is ensured by unique signalling features. A range of colours and accessories is available.



Standard Features

- Addressable manual call point
- LED alarm indicator
- Tamper resistant break glass design
- Easy to test with auto reset
- Fast response
- IP67 waterproof model available

DM2010

2000 Series Addressable Manual Call Point (RED)

Specifications

Power supply

Operating voltage	17-28 VDC
Voltage modulation	4-9 V

Current consumption

Quiescent	< 250 microA
Alarm	< 2.5 mA

Environmental

Operating temperature	-10°C to +70°C
Storage temperature	-20°C to +70°C
Operating humidity	10-95 %
Ingress Protection	IP24D

Physical

Cable specification	0.8 to 2.5 mm ²
Dimensions (L x W x H)	89 x 93 x 27.5 mm
Weight	188 g

Ordering Information

Part No.	Description
DM2010	2000 Series Addressable Manual Call Point (RED)
DMN782	Hinged transparent MCP protection cover
DM783	BZB black bezel
DM790	Flush mount cradle with connectors
DM795	Flush mount cradle, connectors & forkgrrips
DMN798	Breakable Seal for DM2010, DMN700, DMN900 and KAL455 Series Manual Call Points
DMN800	Resettable Element for DM2010, DMN700, DMN900 and KAL450 Series MCPs

